

Tés multivoies à embranchements en EP

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :


Données techniques

Material	Engineered Polymer
End type 2	ProPEX 1/2"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Informations sur le produit et utilisation de l'application

Engineered polymer (EP) branch multi-port tees are used in hot and cold domestic potable water distribution systems. The multi-port tees are available with 3/4" or 1" ProPEX® inlets and 1/2" ProPEX outlets. 1

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Nom de la pièce	Numéro de pièce	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	End Type 1	Weight per UOM [kg/UOM]
3/4" EP Branch Multi-port Tee, 3 (1/2") outlets	Q2237550	112.52	24.26	15.88	31.75	12.19	18.26	41.63	30.99	ProPEX 3/4"	0.045
3/4" EP Branch Multi-port Tee, 4 (1/2") outlets	Q2247550	145.54	24.26	15.88	31.75	12.19	18.26	41.63	30.99	ProPEX 3/4"	0.059
1" EP Branch Multi-port Tee, 4 (1/2") outlets	Q2241050	169.95	30.25	19.69	31.75	15.24	18.26	47.73	37.59	ProPEX 1"	0.077
3/4" EP Branch Multi-port Tee, 6 (1/2") outlets	Q2267550	226.12	24.26	15.88	31.75	11.62	18.26	41.25	29.97	ProPEX 3/4"	0.082
1" EP Branch Multi-port Tee, 6 (1/2") outlets	Q2261050	234.98	30.25	15.88	31.75	14.48	18.26	51.04	36.60	ProPEX 1"	0.113

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Tés multivoies à embranchements en EP	All	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	ASTM E814 ULC S115 ASTM F877 ASTM F1960 CSA B137.5 ULC S102.2 ASTM E119 UL 263 NSF-61 ULC S101 NSF-14	IAPMO-ES HUD MR 1269 ICC-ES-PMG cNSFus-pw UL U.P.Code cQAlus P321

L'installation	Applications connexes
For a mounting bracket, use any product designed to mount 1" copper pipe for the 3/4" multi-port tee or 1 1/4" copper pipe for the 1" multi-port tee. For more information, refer to the Uponor Piping Systems Installation Guide.	PEX-a Plumbing Systems

Notes de bas de page	Coordonnées de la personne-ressource
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517