

Collecteurs à valves en cuivre avec vannes à bille ProPEX

Renseignements sur le projet

|                             |                     |
|-----------------------------|---------------------|
| Nom du poste :              | Lieu :              |
| Ingénieur :                 | Date de soumission: |
| Entrepreneur :              | Présentée par:      |
| Représentant du fabricant : | Approuvé par :      |

Données techniques

|                         |                                                                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                | Copper                                                                                                                                                 |
| Manifold size           | 2 inch                                                                                                                                                 |
| Temp/pressure ratings   | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar)<br>210 °F (99 °C) at 149 psi (10.3 bar) |
| Max. fluid flow rate    | 45 gpm                                                                                                                                                 |
| Prop 65 label required? | Yes                                                                                                                                                    |



Informations sur le produit et utilisation de l'application

The 2" Copper Valved Manifold with ProPEX® Ball Valves is used for radiant heating projects.1 The manifold has a 2" copper sweat fitting adapter supply connection and ¾" nominal branches. This 12-outlet manifold is preassembled with 5/8" or ¾" ProPEX ball valve connections.

| Nom de la pièce                                                         | Numéro de pièce | A [mm]  | B [mm] | C [mm] | Cv Branch | End Type 1  | Weight per UOM [kg/UOM] |
|-------------------------------------------------------------------------|-----------------|---------|--------|--------|-----------|-------------|-------------------------|
| 2" x 4' Copper Valved Manifold with 5/8" ProPEX Ball Valves, 12 outlets | Q2811263        | 1219.20 | 156.17 | 58.89  | 7         | ProPEX 5/8" | 7.031                   |
| 2" x 4' Copper Valved Manifold with 3/4" ProPEX Ball Valves, 12 outlets | Q2811275        | 1219.20 | 158.18 | 58.89  | 7.3       | ProPEX 3/4" | 7.031                   |

| Nom de la pièce                                           | Numéro de pièce | Les codes | Normes               | Annonces   |
|-----------------------------------------------------------|-----------------|-----------|----------------------|------------|
| Collecteurs à valves en cuivre avec vannes à bille ProPEX | All             | -         | CSA B137.5 ASTM F877 | cNSFus-rfh |

L'installation

Any product designed to mount 2" copper pipe may be used as a mounting bracket. Refer to the Uponor Radiant Installation Handbook for additional information. Accessories: 2" Copper Manifold End Cap (A2402000).

Applications connexes

Radiant Heating and Cooling Systems

Remarques :

Ball Valve Cv:  
" outlet - 7.00  
¾" outlet - 7.30

Notes de bas de page

Coordonnées de la personne-ressource

|   |                                                                                                     |                                                                                                 |
|---|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| - | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008 | Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |
|---|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|