

Valves à bille ProPEX en laiton

Submittal information

Date de soumission:

Project Information


Job name :	Location :
Engineer :	Date de soumission:
Contractor :	Présentée par:
Manufacturer's representative :	Approved by :

Technical Data

Cold working pressure	200.2 psi
Temp./pressure ratings	73°F (23°C) at 160 psi (11 bar)
	180°F (82°C) at 100 psi (6.9 bar)
	200°F (93°C) at 80 psi (5.5 bar)

Product information and application use

Uponor ProPEX® Brass Ball Valve is a cost-effective alternative for radiant heating/cooling and hydronic piping applications. Both ends are manufactured with the ProPEX fitting for connections to Uponor PEX pipe. The full-port valves are compatible with propylene glycol mixtures up to 50%. Stem extensions can be installed to accommodate up to 2" of pipe insulation. Note: ProPEX Brass Ball Valves are not approved for potable-water applications.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	I [inch]	J [inch]
ProPEX Brass Ball Valve 1" PEX x 1" PEX	A3201010	1.181	1.808	2.166	4.47	0.79	0.719	6.74	2.956	1.58	4.17
ProPEX Brass Ball Valve 1 1/4" PEX x 1 1/4" PEX	A3201313	1.445	1.91	2.266	4.47	0.905	0.655	7.17	3.206	1.88	4.8
ProPEX Brass Ball Valve 1 1/2" PEX x 1 1/2" PEX	A3201515	1.704	2.292	2.704	5.57	1.095	0.896	8.67	3.799	2.19	5.7
ProPEX Brass Ball Valve 2" PEX x 2" PEX	A3202020	2.147	2.834	3.374	5.57	1.467	1.103	9.448	4.831	2.915	7.128
ProPEX Brass Ball Valve 1/2" PEX x 1/2" PEX	A3205050	0.709	1.083	1.696	3.37	0.49	0.391	4.77	2.186	0.98	2.5
ProPEX Brass Ball Valve 3/4" PEX x 3/4" PEX	A3207575	0.945	1.51	1.868	3.372	0.63	0.555	5.272	2.498	1.26	3.4
2 3/8" Stem Extension Kit for 1/2" and 3/4" Valves	F5630001	-	-	-	-	-	-	-	-	-	-
2 5/8" Stem Extension Kit for 1" and 1 1/4" Valves	F5630002	-	-	-	-	-	-	-	-	-	-
2 5/8" Stem Extension Kit for 1 1/2" and 2" Valves	F5630003	-	-	-	-	-	-	-	-	-	-

Part name	Part no.	Cv	Weight per UOM [lbs/UOM]	Material	End type 1	End type 2
ProPEX Brass Ball Valve 1" PEX x 1" PEX	A3201010	29	1.3	Brass	ProPEX 1"	ProPEX 1"
ProPEX Brass Ball Valve 1 1/4" PEX x 1 1/4" PEX	A3201313	54.7	1.44	Brass	ProPEX 1-1/4"	ProPEX 1-1/4"
ProPEX Brass Ball Valve 1 1/2" PEX x 1 1/2" PEX	A3201515	68.2	2.12	Brass	ProPEX 1-1/2"	ProPEX 1-1/2"
ProPEX Brass Ball Valve 2" PEX x 2" PEX	A3202020	132.2	4.18	Brass	ProPEX 2"	ProPEX 2"
ProPEX Brass Ball Valve 1/2" PEX x 1/2" PEX	A3205050	7	0.36	Brass	ProPEX 1/2"	ProPEX 1/2"
ProPEX Brass Ball Valve 3/4" PEX x 3/4" PEX	A3207575	18	0.52	Brass	ProPEX 3/4"	ProPEX 3/4"
2 3/8" Stem Extension Kit for 1/2" and 3/4" Valves	F5630001	-	0.31	Brass	-	-
2 5/8" Stem Extension Kit for 1" and 1 1/4" Valves	F5630002	-	0.48	Brass	-	-
2 5/8" Stem Extension Kit for 1 1/2" and 2" Valves	F5630003	-	0.57	LF Brass	-	-

Installation	Related applications
--------------	----------------------

Install valve according to local building code. Do not dismantle. Refer to the Uponor Hydronic Piping Design Assistance Manual (HPDAM) or the Uponor Radiant Floor Heating Installation Handbook for additional information.

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems
- Hydronic Piping Systems

Codes	Standards	Listings
-------	-----------	----------

IMC UMC	ASTM F1960 CSA B137.5 NSF-14 ASTM F877 NSF-359	cNSFus-rfh
---------	------------------------------------------------	------------

Trademark Information	Contact information
-----------------------	---------------------

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.636.9517