

# Accessoires PROPEX pour gicleur d'incendie ProPEX en laiton sans plomb (LF)



Submittal information

Date de soumission:

## Project Information

Job name :	Location :
Engineer :	Date de soumission:
Contractor :	Présentée par:
Manufacturer's representative :	Approved by :

## Technical Data

End type 1	ProPEX 1/2"
Temp./pressure ratings	73°F (23°C) at 160 psi (11 bar) 180°F (82°C) at 100 psi (6.9 bar) 200°F (93°C) at 80 psi (5.5 bar)



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]	Equivalent length branch [ft]	Material
Fire Sprinkler Adapter Mounting Bracket, 3/4" and 1"	A7750700	3.171	2.484	1.839	0.17	-	Metal
Fire Sprinkler Adapter Push-on Nut, 25/pkg.	F7000005	2.125	0.233	2.125	0.01	0	Steel
Screws, #10 x 1 1/2", Pan Head, Full Thread, 100/pkg.	F7001500	-	-	-	-	-	-

Installation	Related applications
-	AquaSAFE™ Fire Safety Systems

Codes	Standards	Listings
-	UL 1821	-

Trademark Information	Contact information		
ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.	<table border="0"> <tr> <td>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</td> <td>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.636.9517</td> </tr> </table>	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.636.9517
Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.636.9517		