



**MLCP Tools**



# Uponor Cutting & Preperation

## Uponor Multi pipe cutting tool

- outside diameters 32-40 mm



Item no.	Dimension		Qty 2	Qty 1	UOM
<b>1089677</b>	32-40		12	1	pce
<b>1089779</b>	32-40	blade	50	1	pce

## Uponor Multi pipe cutting tool

- outside diameters 25-63 mm



Item no.	Dimension		Qty 2	Qty 1	UOM
<b>1089675</b>	25-63		12	1	pce
<b>1089777</b>	25-63	blade (wheel)	50	1	pce

## Uponor Multi pipe cutting tool

- outside diameters 50-125 mm



Item no.	Dimension		Qty 2	Qty 1	UOM
<b>1089676</b>	50-125		8	1	pce
<b>1089778</b>	50-125	blade (wheel)	50	1	pce

# Uponor Cutting & Preperation

## Uponor MLC pipe cutting + deburring tool



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1014334</b>	63-110	32	1	pce
<b>1014320</b>	63-110 blade (wheel)	100	1	pce

## Uponor MLC bevelling tool

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.
- Supplied with manual toggle. Without manual toggle to be used as attachment for self-driving screw with tapping screw thread.



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1006830</b>	16	50	1	pce
<b>1015749</b>	20	1200	1	pce
<b>1015756</b>	25	960	1	pce
<b>1015762</b>	32	900	1	pce

## Uponor MLC bevelling tool



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1006638</b>	40	600	1	pce
<b>1015808</b>	50	600	1	pce
<b>1014339</b>	63	600	1	pce
<b>1014344</b>	75	600	1	pce

## Uponor MLC bevelling tool

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1015739</b>	16/20/25	60	1	pce

## Uponor MLC deburring tool universal



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1060167</b>		50	1	pce

# Uponor Cutting & Preperation

## Uponor MLC bending spring inside

- bending spring for Uponor Uni Pipe PLUS and MLC pipes.



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1013729</b>	16	100	1	pce
<b>1013734</b>	20	75	1	pce
<b>1013737</b>	25	50	1	pce
<b>1013739</b>	32	40	1	pce

## Uponor MLC bending spring outside

- bending spring for Uponor Uni Pipe PLUS and MLC pipes.



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1006639*</b>	14	550	1	pce
<b>1006640</b>	16	55	1	pce
<b>1013792</b>	20	45	1	pce
<b>1013794</b>	25	45	1	pce

## Uponor Uni Pipe PLUS bending tool

- producing evenly formed bends in Uponor Uni Pipe PLUS pipes with outer diameters up to 32 mm.

- Delivered complete in tool case with bending segments.



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1071925</b>	16-32	100	1	pce

# Uponor Pressing

## Uponor S-Press manual tool w/o inserts

- in conjunction with exchangeable inserts
- Supplied in case without exchangeable inserts



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
<b>1015764</b>	16-20	16-20	100	1	pce

## Uponor S-Press manual tool insert

- For inserting into the manual pressing tool



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
<b>1015777</b>	16	16	50	1	pce
<b>1015780</b>	20	20	50	1	pce

## Uponor S-Press tool UP110 without jaws

- supplied in carrying case, complete with battery and charger unit
- without pressing jaws.
- Range of application up to 110 mm.

Technical specifications:

- Quick pressing due to short pressing cycle
- Crimping force: linear thrust of approx. 32 kN
- Battery capacity: High-power Makita 3.0 Ah Li-Ion battery
- Charging time: 22 min
- Weight incl. battery: without jaw 3.5 kg
- Dimensions tool: 366 x 81 x 317 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1083612</b>		20	1	set

## Uponor S-Press battery UP110

- Akku 18 V / 3,0 Ah, Li-Ion (54 Wh)
- Battery voltage: 18 V
- Battery capacity: 3.0 Ah
- Charging time: With SPI S-PRESS BATTERY CHARGER: 22 min
- Cell technology: Li-Ion
- Weight: 0,6 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1083608*</b>		18	10	1	pce

# Uponor Pressing

## Uponor S-Press battery charger

- Quick-charger for 18V Li-Ion batteries, 230 V
- Charging time: 1.3 Ah 15 min,  
3.0 Ah 22 min
- Mains supply: 230 V AC
- Voltage range: 18 V
- Weight: 1,0 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1083610*</b>	Mini2, UP110	230	72	1	pce

## Uponor S-Press electric tool w/o jaws UP75

Technical specifications:

- Weight: 3.30 kg
- Nominal voltage: 230 V AC / 50 Hz
- Nominal capacity: 200 Watt
- Press power: ca. 32 kN
- Press duration: ca. 7 sec.



Item no.	Dimension	d mm	OV V	Qty 2	Qty 1	UOM
<b>1007082</b>		- 110	230	20	1	pce

## Uponor S-Press spare battery UP75

- for the battery powered pressing machine UP 75
- Not compatible to the Ni-Cd charger unit.



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1006949*</b>		12	12	1	pce

## Uponor S-Press spare charger Mini UP75

- or the re-chargeable battery of the pressing machine UP 75 and Mini KSP0



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1006950</b>		230	10	1	pce

## Uponor S-Press jaw UPP1

- pressing jaws for Uponor MLC press fittings



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
<b>1007084</b>	16	16	216	1	pce
<b>1007086</b>	20	20		1	pce
<b>1007087</b>	25	25		1	pce
<b>1007088</b>	32	32		1	pce

# Uponor Pressing

## Uponor S-Press jaw UPP1

- pressing jaws for Uponor MLC press fittings



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
<b>1015768</b>	40	40	108	1	pce
<b>1015792</b>	50	50	108	1	pce

## Uponor S-Press base unit for chain

- Base unit for the pressing chain to press Uponor MLC press fittings 63 - 110 in conjunction with the pressing tool UP 110, UP 75 and UP 75 EL



Item no.	Dimension	d mm	Qty 1	UOM
<b>1046545</b>	63-110	63-110	1	pce

## Uponor S-Press chain

- pressing chain to be used together with the Base unit to press Uponor MLC press fittings 63 - 110 in conjunction with the pressing tool UP 110, UP 75 and UP 75 EL



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
<b>1046541</b>	63	63	72	1	pce
<b>1046542</b>	75	75	72	1	pce
<b>1046543*</b>	90	90	72	1	pce
<b>1046544*</b>	110	110	54	1	pce

# Uponor Pressing

## Uponor S-Press tool Mini2 with KSP0 jaw

- Uponor S-Press tool Mini<sup>2</sup> supplied in carrying case, complete with battery and charger unit and pressing jaws.
- Range of application up to 32 mm.

### Technical specifications:

- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.3 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1083586</b>	16/20/25/32	30	1	set

## Uponor S-Press tool Mini2 with KSP0 jaw

- Uponor S-Press tool Mini<sup>2</sup> supplied in carrying case, complete with battery and charger unit and pressing jaws.
- Range of application up to 25 mm.

### Technical specifications:

- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.3 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1083594</b>	16/20/25	25	1	set



# Uponor Pressing

## Uponor S-Press tool Mini2 without jaws

- Uponor S-Press tool Mini<sup>2</sup> supplied in carrying case, complete with battery and charger unit.
- Range of application up to 32 mm.

Technical specifications:

- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.5 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 1	UOM
<b>1085388</b>		1	pce

## Uponor S-Press tool Mini2

- Uponor SPI S-Press tool Mini<sup>2</sup> without carrying case, without battery and charger unit and without pressing jaws.



Item no.	Dimension	Qty 1	UOM
<b>1087260</b>		1	pce

## Uponor S-Press battery Mini2

- Battery 18 V / 1.5 Ah, Li-Ion (27 Wh)
- Battery voltage: 18 V
- Battery capacity: 1.5 Ah
- Charging time: With SPI S-Press Battery Charger: 15 min
- Cell technology: Li-Ion
- Weight: 0,4 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1083605</b>		18	48	1	pce

## Uponor S-Press battery charger

- Quick-charger for 18V Li-Ion batteries, 230 V
- Charging time: 1.3 Ah 15 min,  
3.0 Ah 22 min
- Mains supply: 230 V AC
- Voltage range: 18 V
- Weight: 1,0 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1083610*</b>	Mini2, UP110	230	72	1	pce

# Uponor Pressing

## Uponor S-Press battery Mini

- Battery: 9.6V for Uponor battery pressing tool Mini KSP0.



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
<b>1015703</b>		9,6	120	1	pce

## Uponor S-Press jaw Mini KSP0

- Uponor pressing jaws MLC Mini KSP0



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
<b>1007091*</b>	16	16	5	1	pce
<b>1007093*</b>	20	20	5	1	pce
<b>1007094*</b>	25	25	5	1	pce
<b>1007095*</b>	32	32	5	1	pce

# Uponor Accessories

## Uponor Smart Aqua mounting rack bending tool

- For bending the 2 meter long mounting track.



Item no.	Dimension	Qty 2	Qty 1	UOM
<b>1015424</b>	2m	100	1	pce

## Uponor plastic pipe bend support

Made of impact resistant plastic as bend support 90° bends.



Item no.	Dimension	d mm	r mm	Qty 2	Qty 1	UOM
<b>1009004</b>	16	16	90	2340	10	pce
<b>1009233</b>	20	20	100	2340	10	pce

## Uponor Galvanised Steel pipe bend support

Made of galvanised steel as bend support 90° bends.



Item no.	Dimension	d mm	r mm	Qty 2	Qty 1	UOM
<b>1009006</b>	25 Galv. Steel	20	90	5000	20	pce

# uponor

**Uponor GmbH**

P.O. Box 1641  
97433 Hassfurt  
Germany

**T** +49-(0)9521 690 0  
**F** +49-(0)9521 690 750  
**E** [international@uponor.com](mailto:international@uponor.com)

Australia

**T** +61 (0)7 3202 6831  
**M** +61 (0)477 136 977  
**E** [international@uponor.com](mailto:international@uponor.com)

01/2024



[www.uponor.com](http://www.uponor.com)