

Date:
2005-08-25

No:
4022

Replaces licence no.:

Licensee's name and address

Uponor Suomi Oy
PL 21
15561 NASTOLA
FINLAND

Marks covered by licence:



Information regarding licensee/manufacture

Licensee's technical officer Jaana Hallikas	Telephone +358 (0)20 129 211	Telefax +358 (0)20 129 210
	E-mail jaana.hallikas@uponor.com	
Manufacturer	Place of manufacture Fristad, Sverige	

Product covered by the licence

Type of product Plaströr	Standard / Other Normative document EN 1329-1	Specific rules SBC 1329
Specification of product PVC-avloppsrör enligt bilaga 1 Godkända råmaterial och tätningar enligt bilaga 2 (konfidentiell) Besiktning av tillverkningsstället: SP F319916		

SFS-Inspecta Certification hereby gives the above licensee permission to use the INSTA-CERT mark on or in connection with products which fulfil the requirements of the standard or the normative document specified above (what is said in this document about INSTA-CERT mark will also be valid for marks defined in relevant SBC). The certification licence is valid on the condition that the licensee complies with the "General rules for certification by partners of INSTA-CERT" (GRC) and the specific rules applying to certification of products of the type mentioned. The licensee is obliged to indemnify INSTA-CERT of any claim for damages or any other expenses to which partners of INSTA-CERT may become liable as a result of injuries caused by a product manufactured or sold by the licensee. This also applies to defective or faulty products.

The licence is valid for one calendar year and is automatically renewed for one year at a time, unless the licensee or member of INSTA-CERT gives at least three months notice to the contrary.

The licence is not transferable.

MEMBER OF INSTA-CERT:
SFS-INSPECTA CERTIFICATION


Harry Lindström, Managing Director

Certifieringslicens nr 4022

Datum 2005-08-29

Licensinnehavare

Uponor Suomi Oy
NASTOLA, FINLAND

PVC-avloppsrör

RÖR:

TESTRAPPORTER OCH
ANDRA
REFERENSDOKUMENT:

Produktnamn

UPONAL HT

Användningsområde /
Ringstyvhet

B / SN8

SITAC 1003/75

Dimensioner, mm

- storleksgrupp 1

50

Användningsområde /
Ringstyvhet

BD / SN8

Dimensioner, mm

- storleksgrupp 2

75 - 110

Beteckning på tillverkningstället

5