



NATIONAL DECLARATION OF PERFORMANCE
No. 3/2020

- 1. Name and trade name of the construction product:**
Bathroom point inlet
- 2. Marking of the construction product type:**
AQUA AMBIENT SUPER bathroom point inlet DN 50 pass-through with ARCO, SPOT, CUBE, ORIENT grates
- 3. Intended use or uses:**
AQUA AMBIENT SUPER inlets are used to drain household wastewater from floor surfaces of wet rooms.
- 4. Manufacturer's name and address and product manufacture place:**
CAPRICORN S.A.
58-160 Świebodzice
Ciernie 11
- 5. Name and address of the authorised agent, if any:**
not applicable.
- 6. National system used for the assessment and verification of the constancy of performance:**
system 4.
- 7. National technical specification:**
National technical assessment:
ITB-KOT-2020/1504 rev. 1 - Aqua Ambient Super, Aqua Ambient and Aqua Ambient Black Line bathroom drain inlets.

Technical Assessment Body / National Technical Assessment Body:
N/A

8. Declared performance:

Essential characteristics of the product for the intended use or uses	Declared performance	Comments
Load resistance	Class K3 – 300 kg	-
Blockage prevention	Meets the requirements	-

Capricorn S.A.
Ciernie 11, 58-160 Świebodzice

Head Office
sekretariat@capricorn.pl
Phone: +48 74 854 05 16
fax: +48 71 722 28 18

Export Department
sales@capricorn.pl
Phone: +48 74 8503 546

Domestic Sales
zamowienia@capricorn.pl
Phone: +48 74 8503 528
+48 74 8503 551

fax +48 74 85 03 535

www.capricorn.pl

NIP (Tax Identification Number): 884-002-16-00, Regon (National Business Registry No.): 891489258

District Court for Wrocław-Fabryczna in Wrocław

9th Commercial Division of the National Court Register: 0000472600,

Share capital: PLN 400,000.00

ALIOR BANK S.A SWIFT (BIC) ALBPPLPW
IBAN: PL49 1060 0076 0000 3210 0015 3728 (CURRENCY PLN)
IBAN: PL65 1060 0076 0000 3210 0015 3731 (CURRENCY EUR)



Inlet flow rate: - at a head of water of 20 mm - at a head of water of 10 mm	≥ 0.40 l/s ≥ 0.30 l/s	-
Body water tightness	No leaks under pressure of up to 10 kPa over a period of at least 15 minutes	-
Odour-tightness	Pressure drop ≤ 20 Pa over a period of at least 15 minutes	-
Temperature cycling	The inlets are resistant to intermittent wastewater temperature in the range of 15 ± 10°C to 93±2°C	-
Water seal depth of the inlets	≥ 50 mm	-
Resistance of water seal to pressure	≥ 400 Pa	-
Self-cleansing capacity	Meets the requirements	-

9. The performance of the product specified above are compliant with all the declared performance listed under item 8. This National Declaration of Performance has been issued pursuant to the Act of 16 April 2004 on Construction Products under the sole responsibility of the manufacturer.

On behalf of the manufacturer, signed by:

Monika Piekarz

Member of the Management Board for Production

CAPRICORN S.A.
Członek Zarządu ds. Produkcji

Monika Piekarz

Świebodzice, 6/10/2020
(place and date of issue)

.....
(signature)

Capricorn S.A.
Ciernie 11, 58-160 Świebodzice

www.capricorn.pl

Head Office
sekretariat@capricorn.pl
Phone: +48 74 854 05 16
fax: +48 71 722 28 18

Export Department
sales@capricorn.pl
Phone: +48 74 8503 546

Domestic Sales
zamowienia@capricorn.pl
Phone: +48 74 8503 528
+48 74 8503 551

fax +48 74 85 03 535

NIP (Tax Identification Number): 884-002-16-00, Regon (National Business Registry No.): 891489258

District Court for Wrocław-Fabryczna in Wrocław

9th Commercial Division of the National Court Register: 0000472600,

Share capital: PLN 400,000.00

ALIOR BANK S.A SWIFT (BIC) ALBPPLPW
IBAN: PL49 1060 0076 0000 3210 0015 3728 (CURRENCY PLN)
IBAN: PL65 1060 0076 0000 3210 0015 3731 (CURRENCY EUR)