

Projekts

IKEA



Uponor iesaiste



18.000 m²

IKEA

The IKEA homestore in Rothenburg in the Canton of Lucerne, uses the TABS Thermally Active Building System from Uponor to cater for heating and cooling requirements.

Projekta fakti:

Location
Rothenburg,
Switzerland

Pabeigts
2011

Ēkas tips
Publiskās ēkas

Product systems
Apkure & Dzesēšana

Adrese
Wahligenstrasse
6

Mājas lapa
http://www.ikea.com/ch/de/store/rothenburg/?cid=ch|ps|branded|brand|go|ikea_rothenburg|de|search

Projekta
veids
Renovation

Partneri

Bauherr:

IKEA Supply AG, Grüssenweg 15,
4133 Pratteln, Switzerland

Installateur:

Cofely AG, Schweighofstrasse 14,
6010 Kriens, Switzerland

Planer:

Haustec Engineering AG, Güterstraße
5, 3072 Ostermündingen, Switzerland

Covering around 18,000 m² of sales space, the IKEA homestore in Rothenburg in the Canton of Lucerne provides a pleasant atmosphere for its customers. In order to provide a cosy level of heat on cold days and a pleasantly cool climate in hot weather, the concrete ceilings of the building were fitted with the TABS Thermally Active Building System from Uponor, covering an area of 20,795 m². Haustec Engineering AG in Ostermündingen planned the energy concept for the first IKEA homestore in central Switzerland.

Uponor installed 96,600 m of Uponor PE-Xa 20 x 2.3 mm pipe on behalf of trade specialists Cofely AG, Kriens. The pipes were installed locally on the concrete reinforcement, spaced at 15 cm apart. In addition, the specialist tradesmen fastened the PE-Xa pipes in place using Uponor fixing tracks. This meant that the pipes could be laid quickly and the follow-up work could be carried out quickly. The concrete structure was then cast. Compared to conventional air conditioning systems, Uponor TABS saves up to 50 percent of investment and operating costs. There is also no need for troublesome radiators. In addition, the components are practically maintenance-free.

The IKEA homestore in Rothenburg is heated and cooled in an energy-efficient way using Uponor TABS - also avoiding draughts. Hot or cold water flows through the pipes, heating or cooling the concrete ceiling. To provide cooling, the ceilings absorb the heat generated during the course of the day. During the night, the circulating water dissipates this heat, cooling the rooms and avoiding unwanted temperature variations caused by internal and external loads. The heat or cold stored in the ceilings between the floors is largely dissipated through radiation, as well as being partially returned to the space through convection.

The advantage is that, owing to the large activated areas, building activation allows heat to be supplied or dissipated efficiently even at low flow temperatures. The TABS system at IKEA in Rothenburg provides heat at a flow temperature of 30 °C and a return of 26 °C and cools at a flow temperature of 19 °C and a return of 23 °C. TABS thus achieves a heat output of about 35 W/m² and cooling of about 40 W/m².

IKEA





+GF+

Adrese

Uponor Latvia SIA
Ulbrokas 34
Rīga, LV-1021
Latvija

Tālrunis +37167821321

E-pasts

jautajums.lv@georgfischer.com

W www.uponor.com