

Referências



## Alibaba headquarters

Envolvimento da Uponor



5,000sqm

## Alibaba headquarters

Mr. Ma Yun spent one billion RMB to make Alibaba headquarters a luxury modern architecture.

Mr. Ma Yun spent one billion RMB to make Alibaba headquarters a luxury modern architecture. It is the first time Alibaba built the working park by their own. Uponor underfloor system was installed 5,000 square meters for senior management offices in Alibaba headquarters.

### Dados do projeto:

Location Conclusão

Hangzhou, China 2016

Tipo de edifício Product systems

Edifício de escritórios Climatização Invisível

Tipo de projeto

Novo edifício

Mr. Ma Yun spent one billion RMB to make Alibaba headquarters a luxury modern architecture. It is the first time Alibaba built the working park by their own. Uponor underfloor system was installed 5,000 square meters for senior management offices in Alibaba headquarters.

The design of the building is in accordance with the LEED gold certification standards. In order to develop the spirit of continuous innovation, the owners require all building materials to have energy saving and environmental protection effects. We use PE-Xa and stainless steel manifolds to provide ground radiation heating and cooling system for the building. Uponor PE-Xa has high flexibility and good wear resistance, which can stand the harsh conditions in construction site. It can also stand high temperature and high pressure. Uponor is the first company to produce PE-Xa pipe by engel process. Uponor PE-Xa pipe has five layers. It has two more layers than the other PE-Xa pipe on the market.

The base layer is crosslined, which is produced according to the requirements of PE-Xa pipe standard. It has the characteristics of durability, impact resistance and stress cracking resistance. The second layer acts like an adhesive to the base layer and the third oxygen barrier. The third layer prevents oxygen from penetrating into the radiant heating and cooling system. The fourth layer acts as a bond between PE outer protective layer and the oxygen barrier. The fifth PE layer is an outer protective layer to prevent the pipe from the damage caused by the leakage of oxygen, especially when installing on the surface of the concrete floor.

Uponor stainless steel manifold has the advantages of high corrosion resistance, high sanitation and strong impact resistance. The coefficient of thermal expansion is close to that of brass. The valve can be rotated and is easy to connect the drain pipe.

Uponor system is extremely safe and reliable, almost free of maintenance, making it the first choice of ground radiant heating and cooling system.

We actively cooperate with on-site construction team. The customers are very satisfied with the concise design style of the whole space that create a comfortable and pleasant office environment for employees.

## Alibaba headquarters



Uponor em Portugal

Uponor Portugal, Lda.

Telefone +351 227 860 200

Rua Jardim 170 R/C Esquerdo -fração

E-mail

B

servicioalcliente.es.bfs@georgfischer.com

4405 - 823 Vilar Paraíso - Vila Nova de

W www.uponor.com

Gaia