

Referencie

## D'or Appartements



### Uponor participácia



6000

## D'or Appartements

In one of the most beautiful parts of Budapest, at the bottom of the Sas hill, there is this 88 flat condominium called "D'or Appartements", which consists of 3 blocks. On the 1.23 acre property, there are three 5-story blocks of 32, 31 and 25 flats respectively. The most important aspect in the design of the flats was to create ideal living-space, thus homes between 46 m2 and 105 m2 can be found in the buildings.

### Fakty o projekte:

Location

Budapest, Hungary

Dokončenie

2011

Typ budovy

Rodinné domy

Product systems

Sálavé vykurovanie a chladenie

Adresa

D'or Appartements 88 lakásos  
társasház

Typ projektu

Novostavba

## Partneri

### specifier

Colt Hungária Kft.  
1103 Budapest Gyömrői u. 156.

### installer

Deák és Társa Kft.  
1222 Budapest, Vöröskereszt utca 2.

### investor

D or Appartements Kft.  
1118 Budapest Dayka G. u. 3.

---

## Lifelong Quality

In the architectural design, functionality and aesthetics were the main drivers. An important role was given to the building-up large glass surfaces and galleries, which let vital sunshine inside of the flats. On the first floor flats are complemented with their own gardens, providing an even more homely environment. On the top floor, flats have large roof-gardens, which dazzle their owners with unique panorama. In the dreaming-up of the flats, it was an important aspect to create a harmonic environment of buildings and green areas. In the condominium surrounded by a fence, the security of the occupants is increased by state-of-the-art video entry phone and electrically operated garage doors. In the design of the building engineering system, the exceptional comfort and energy efficiency was taken into account. Among others, investor demanded construction of the cooling system, too. It was a plausible demand that the two functions are solved by the same system. This is why Uponor wall and ceiling heating/cooling system had been chosen, which - due to its small installation thickness - was installed in the plaster layer. Hence, heating/cooling tasks are solved invisibly. The 9.9 mm Uponor PE-Xa pipes were installed to the ceiling using clamp joint rails, fixed at every twenty inches. The cold or hot water circulation in these pipes provide the proper room temperatures. 4,500 m<sup>2</sup> Uponor wall and ceiling heating/cooling system were installed, containing nearly 45,000 m Uponor 9.9 mm diameter Uponor Pe-Xa pipes. Due to the low operating temperature, the system is energy efficient.

## D'or Appartements





# +GF+

Kontaktujte nás

Uponor, s.r.o.  
Vajnorská 105  
831 04 Bratislava  
Slovenská republika

Telefón +421 232 111 300  
E-mail  
[zakaznicky servis.cz.sk.bfs@georgfischer.com](mailto:zakaznicky servis.cz.sk.bfs@georgfischer.com)  
W [www.uponor.com](http://www.uponor.com)